

SECTION:A-A

RECOMMENDED P.C.B LAYOUT

MATERIAL SPECIFICATION:

1. HOUSING:HEIGHT TEMP. PLASTIC(UL94V-0)
2. CONTACT:COPPER ALLOY
3. SHELL:STAINLESS STEEL


ELECTRICAL PERFORMANCE

1. CURRENT RATING: SIGNAL(PINS 2,3,4): 0.5A;
POWER(PINS 1,5): 1.8A
2. RATED VOLTAGE(MAX.):250 VOLTS AC (RMS)
3. DIELECTRIC STRENGTH:500V AC FOR 1 MINUTE BETWEEN ADJACENT TERMINAL, NO BREAKDOWN
4. INSULATION RESISTANCE:1000 MEGOHMS MIN. 500V DC FOR 1 MINUTE BETWEEN ADJACENT TERMINAL
5. CONTACT RESISTANCE:30 MILLIOHM MAX.
6. OPERATING TEMPERATURE:-25° to +85°

ORDERING INFORMATION

U 6 F 05 E - C X T 2 - B 15
(1)(2)(3) (4) (5) (6)(7)(8)(9) (10)(11)

1. SERIES NO.
2. USB TYPE
3. USB MALE & FEMALE TYPE
4. NUMBER OF PIN
5. TAIL CONSTRUCTION TYPE
6. HOUSING COLOR
7. CONTACT PLATING
8. SHELL PLATING
9. PLASTIC ORIENTATION POST TYPE
10. B TYPE OR AB TYPE
11. SUFFIX NO.1



G	5.0			DRAWING:	GENERAL TOLERANCE			CHIN-BAN electronics (H.K) co., ltd	
	4.0				Bains	.X:±0.30 .X°:±2° .XX:±0.20 .XX°:±1° .XXX:±0.10 .XXX°:±0.5°			
H	3.0			CHECKED:	UNIT: MM	PROJECTION:	DESCRIPTION:	Micro USB 2.0 Conn. Female B Type	
	2.0			Tian Hai					SCALE: 1/1
	1.0			APPROVAL:	SHEET: 1/1		DRAWING NO: UK0073	SIZE: A4	
	NO.	DATE	DESCRIPTION	APPROVAL					
	1		2	3	4	5	6	7	8