

ROHS

0.35±0.05

W±0.15

4.00

12.00

FIRST APPROXIMATELY
20PCS EMPTY CARRIER

PACKING N PCS PRODUCT(REFER TO TABLE)

THE END APPROXIMATELY
20PCS EMPTY CARRIER

300mm min

THE DIRECTION OF PRODUCT PACKING

产品标签
(1PCS/REEL)

PROTECTION TAPE

DESICCANT 1PCS

VACUUM BAG

VACUUM BAG
(450x490x0.15)

产品标签
(1PCS/BOX)

DETAIL "F"

COVER TAPE

卷带圆孔朝上

OUTER Ø330

CARRIER TAPE

ø23

ø13.5

DETAIL :F-F

N PCS/REEL

N PCS REELS

TOTAL N LAYERS

TRIANGLE LINER (4PCS)

CARTON

PULL OUT DIRECTION

PULL OUT DIRECTION


10°

PACKING INFORMATION:

PART NAME	W	PCS/REEL	REEL/CARTON	TOTAL	CARTON
B1M10U-C1R-R	16.0	800 PCS	6 PCS	4.8K PCS	350*350*160mm
B1M16U-C1R-R		1300 PCS	5 PCS	6.5K PCS	
B1M20U-C1R-R	1300 PCS	5 PCS	6.5K PCS		
B1M24U-C1R-R	1200 PCS	5PCS	6.0K PCS		
B1M26U-C1R-R	800 PCS	5 PCS	4.0K PCS		
B1M30U-C1R-R	24.0	1500 PCS	5 PCS	7.5K PCS	
B1M32U-C1R-R		1500 PCS	5 PCS	7.5K PCS	
B1M34U-C1R-R		1300 PCS	5 PCS	6.5K PCS	
B1M36U-C1R-R		800 PCS	5 PCS	4.0K PCS	
B1M40U-C1R-R		800 PCS	5 PCS	4.0K PCS	

NOTE:
1. PEELING OFF FORCE OF TOP TAPE: 40~100g
(PEELING DIRECTION AS SHOWN IN FOLLOWING FIG.)
THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT
PEEL OFF SHOULD NOT BE ALLOWED, DURING TRANSPORTATION.

2. MATERIAL:
CARRIER TAPE: POLYSTYREN(P.S)
TOP TAPE: PE
REEL TAPE: POLYSTYREN(P.S)



G	5.0				
	4.0				
	3.0				
	2.0				
H	1.0	2016.06.26	NEW	Tian hai	
	NO.	DATE	DESCRIPTION	APPROVAL	

DRAWING:
Henry

CHECKED:

APPROVAL:

GENERAL TOLERANCE


.X:=±0.50 .X*:=±2°
.XX:=±0.30 .XX*:=±1°
.XXX:=±0.20 .XXX*:=±0.5°

UNIT: MM

PROJECTION:

SCALE: 1/1

SHEET: 1/1



CHIN-BAN
electronics (H.K) co., ltd

DESCRIPTION:

0.5mm Board to Board Male-PACKING

PART NO: F-B1MXXU-C1R-R

REV: 1.0

DRAWING NO: UT0055

SIZE: A4